


One-way plastic UN-containers approved for dangerous goods



Manufactured in highly resistant polypropylene, the 3H2  containers are UN-approved in 3H2 and are appropriate for packing and transport of solid dangerous goods of packing group II and III. Available colours are basically blue and black. The containers are delivered without danger label.



The hinged lids are identical for the complete range. They are equipped with a hot-melt joint which ensures the maximum leakproofness as well as secure handling right from the permanent closure. Various lid colours are available: white, yellow...

Autoclavable without the lids at 134°C.

LID WITH APERTURE AND BUNG (ref PO...)

Aperture lid (ø 130 mm)

- ✓ temporary and permanent leakproof closure
- ✓ Safe and easy to use (by simply screwing)
- ✓ Patented system



Technical specifications	30L	50C	50L	60L
Ref. lockable plain lid	3H2PP30	3H2PP47	3H2PP50	3H2PP60
Ref. hinged aperture lid	3H2P030	3H2P047	3H2P050	3H2P060
Outer dimensions (mm)	400x330x310	400x330x460	400x330x540	400x330x640
Weight PP - PO (kg)	1,13 - 1,17	1,43 - 1,47	1,55 - 1,59	1,84 - 1,88
ADR UN-approval	3H2/Y20/S/- /F/ BVT31918/PLAZUR	3H2/Y20/S/- /F/ BVT31918/PLAZUR	3H2/Y25/S/- /F/ BVT31918/PLAZUR	3H2/Y30/S/- /F/ BVT31918/PLAZURADR
Maximum gross weight (kg)	20 kg	20 kg	25 kg	30 kg
Markings	Without ADR labelling Engraved UN number			
Advantages	In conformity with EN ISO 23907-1:2019 : integrally attached plain lids & aperture lids; Temporary and permanent closures on both lids versions (plain and with aperture); Central handle attached to the vat and not on the lid to avoid any toppling risk.			
Packing	On pallet with spare pallets of lids (CP: 1296 units/pal of 400 kg or CO + OB: 972 units/pal of 340 kg)			
Quantity of boxes per pallet	342	306	306	270
Pallet dimensions DxWxH (cm)	100/120/250			
Weight vats' pallet (kg)	295	360	395	425

ADVANTAGES **Pacazur** : SIMPLE and SAFE USE

- ✓ Tested **temporary closure system** (ISO 23907-1:2019 certified)
- ✓ User-friendly shape, ergonomic **design**;
- ✓ **Secure handling : lateral lifting** (2 handles) or frontal (1 handle independant from the lid)
- ✓ **Effortlessly permanent closure**: 11 clips, snapped with only 2 fingers;
- ✓ **Exceptional stability** : rectangular shape; bin bottom print on the lid;
- ✓ **Hinged lid** : easy positioning without constraint for final permanent closure (patentend system);
- ✓ Can be used in a stand with foot lid-opening mechanism;
- ✓ Colours, pallets and markings on request.