



4G Box[®]



**4G combination packaging
approved according to the ADR
for the carriage of dangerous goods by road**



Waste containers



4G Box[®]

Designed in strong kraft cardboard and coupled with polyethylene liner, these one way 4G packages are approved for the transport of dangerous goods (packing group II and III).

		25 Litres	50 Litres Low	
Article Ref. (white background)		CT4G25H	CT4G50B	
CARDBOARD BOX	Inner dimensions	230x230x430	280x380x470	
	Outer dimensions	236x236x442	286x386x482	
	Weight (g)	396 g	652 g	
	Cardboard thickness	One-faced corrugated fibreboard 2,9 mm		
	Box Mounting	Quick automatic bottom assembly to avoid complex handling		
BAG	Liner composition	Blue polyethylene with a high thickness of 70 µ.		
	Inner Liner treatment	Antistatic & anti-blocking to ease opening and assembly		
	Liner junction	Waterproof Welding		X
	Liner bonding	Peripheral adhesive dots		X
UN APPROVAL	ADR approval - UN-Number	4G/Y10/S/--/*B/2130-200066	4G/Y15/S/--/B/2130-200059	X
	Max. load Capacity	10 Kg	15 Kg	X
	Box Closure	Temporary by folding, permanent by inserting the inviolability tongue		X
	Liner Closure	Whole in the cardboard protection shield to insert the twisted liner in		X
	Marking	Standard version without any ADR danger diamond. Mounting drawings, UN-approval number, max. Gross weight and filling limit.		X
PACKAGING	Packaging	40 packets of 10 boxes on a pallet		
	Units per pallet	400	400	
	Pallet dimensions (cm)	80x120x180	80x136x190	
	Pallet weight	172 Kg	275 Kg	
	Pallet Protection	Cardboard reinforcements, stretching film		

Product advantages → Regulatory conformity ←

MAIN TECHNICAL SPECIFICATIONS FOR USERS

- ★ Permanent closure eased by an immediately available bond (patented system)
- ★ External handles, triple thickness for secure handling
- ★ Large flaps with protruding bag

